

# SPECIAL WASTE CONTAINER TYPE SAP-1



- For the international transport of solids and paste-like substances according to the ADR/RID/IMDG codes, packing groups I, II and III
- IBC according to standard “DIN 30741-1“
  - construction made of 2 mm steel sheeting, lid and basis frame made of 2.5 mm steel sheeting
  - reinforced edging
  - through fork sleeves
  - sturdy stacking corners with crane eyes
  - suitable for pick-up by pallet-, forklift truck or crane
  - lid: spring-assisted and with a seal
  - 2 lid fasteners, lockable
  - automatic lid lock in 270° position
  - lid support in 70° position
  - max. density 1.5 kg/l
  - finish hot-dip galvanized or with additional painted finish (outside only)



Type SAP 800-1 with dual code (accessory)

- Accessories (please refer to page 138)
- PE foil bag (100 bags/roll)
  - PE inlay
  - embossed company name
  - dual code



Type SAP 800-3 with 2 lid closures, one lockable

§

UN-APPROVALS

11A/X/D/BAUER/6007

4A/X/D/6917-BAUER

| Type      | Volume in l | Dimensions in mm (l x w x h) | Can be stacked | Total permitted weight in kg | Weight in kg |
|-----------|-------------|------------------------------|----------------|------------------------------|--------------|
| SAP 450-1 | 450         | 1200 x 1000 x 835            | 3 units        | 825                          | 150          |
| SAP 600-1 | 640         | 1200 x 1000 x 1053           | 3 units        | 1124                         | 164          |
| SAP 800-1 | 800         | 1200 x 1000 x 1235           | 3 units        | 1375                         | 175          |
| SAP 800-3 | 800         | 1200 x 1000 x 1235           | 3 units        | 1375                         | 175          |

Finish: hot-dip galvanized